

TRANSELF NFJ 75W-80 is adapted to RENAULT vehicles equipped with gearboxes of families J, TL4, NDX.

Technical Data Sheet

International
Specifications

API GL-4

Manufacturers
Approvals

Approved :
RENAULT JXX TRANSMISSION, RENAULT NDX TRANSMISSION,
RENAULT TL4 TRANSMISSION

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

Particularly for vehicles TWINGO, MODUS RENAULT, Clio, Mégane (except(off) Mégane / Scenic II Pk4), and Laguna (except(off) motorization 2, 2DT, dci and V6), for Spaces (2,0 and 1,9 dti) and for Kangoo.

Adapted to the requirements of the mechanical gearboxes of light passenger and utilitarian cars, provided with brass synchro in simple configuration or multi-cones.

2 - Customer Benefits

High-performance transmission fluid that improves speed changing at low temperatures, reduces noise during speed changes, prevents difficult disengagements and cracks.

Provides good protection for gear teeth under severe stress, maintains smooth speed changes throughout the gearbox's lifespan.

Enhances protection against wear on mechanical components.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	884
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	47
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	8.5
Viscosity index	ASTM D2270	-	175
Pour point	ASTM D97	°C	-40
Flash point	ASTM D92	°C	-
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.